United States Patent [19]

Cobb, Jr.

[11] Patent Number:

5,056,892

Date of Patent: [45]

Oct. 15, 1991

[54]	THIN, FLEXIBLE FILM				
[75]	Inventor:	Sanford Cobb. Jr., St. Mary's Poin			

Minn.

[73] Assignee: Minnesota Mining and

Manufacturing Company, Saint Paul,

[21] Appl. No.: 472,621

[22] Filed: Jan. 30, 1990

Related U.S. Application Data

Continuation of Ser. No. 218,087, Jul. 12, 1988, Pat. No. 4,906,070, which is a continuation of Ser. No. 903,655, Sep. 5, 1986, abandoned, which is a continuation-in-part of Ser. No. 799,869, Nov. 21, 1985, abandoned, and a continuation-in-part of Ser. No. 819,118, Jan. 15, 1986, abandoned.

[51]	Int. Cl. ⁵ G02	B 5/04; G02B 5/124;
		G02B 5/136
[52]	U.S. Cl	359/831; 359/528;
		359/546

[58] Field of Search 350/286, 287, 276 R. 350/616, 176, 167, 103, 104, 106, 109; 362/32, 339, 337

[56] References Cited

U.S. PATENT DOCUMENTS

2,175,067	10/1939	Rolph 240/106
2,218,227	10/1940	Winnek 13/61
		Merton 18/57
		Merton 156/10
2,279,555	4/1942	Browne et al 88/24
2,723,919	11/1955	Pohnan 117/35
3,288,990	11/1966	Stahlhut 240/106
3,689,346	9/1972	Rowland 156/245
		Anderson 428/142
4,118,763	10/1978	Osteen 362/339

		•
4,120,565	10/1978	Rabl et al 350/286
4,154,219	5/1979	Gupta et al 126/270
4,235,515	11/1980	Sheiman et al 350/138
4,244,683	1/1981	Rowland 425/143
4,260,220	4/1981	Whitehead 350/96.28
4,389,085	6/1983	Mori 350/96.10
4,422,719	12/1983	Orcutt 350/96.30
4,466,697	8/1984	Daniel 350/96.30
4,497,860	2/1985	Brady, Jr 428/156
4,576,850	3/1986	Martens 428/156
4,615,579	10/1986	Whitehead 350/96.1

FOREIGN PATENT DOCUMENTS

2127344 4/1964 United Kingdom .

Primary Examiner-Bruce Y. Arnold Assistant Examiner-James Phan Attorney, Agent, or Firm-Gary L. Griswold; Walter N. Kirn; Stephen W. Buckingham

ABSTRACT

A thin, flexible film made of a transparent polymeric material including a structured surface and an opposite smooth surface, wherein light striking either surface, within certain angular ranges, is totally internally reflected. The structured surface includes a linear array of miniature substantially right angled isosceles prisms arranged side-by-side to form a plurality of peaks and grooves. In addition, the perpendicular sides of the prims make an angle of approximately 45° with the smooth surface, and when the film is curled the smooth surface lies in a smooth continuous arcuate curve without materially affecting the performance of the film. Because of the film's flexibility and its ability to totally internally reflect light, it may be utilized in a variety of ways, for example, as a collector of solar energy or as a light conduit. The performance of the film may be manipulated to permit controlled light leakage.

8 Claims, 4 Drawing Sheets

